

स्वामी रामानंद तीर्थ ग्रामीण शासकीय वैद्यकीय महाविद्यालय व रुग्णालय, अंबाजोगाई  
( सामान्य भांडार विभाग )

SWAMI RAMANAND TEERTH RURAL Govt. MEDICAL COLLEGE, AMBAJOGAI DIST BEED  
Ph. (02446)245792/248963/249362/248438/FAX-02446/247132 website www.srtrgmca.org email- srtrgmc@gmail.com

NO.SRTRGMCHA/GEN.STORE/ 1518 /2022 DATE - 24 /03/2022

विषय:- यंत्रसामुग्री व साधनसामुग्रीचे दर पत्रक सादर करणे बाबत.

- संदर्भ :- १. जिल्हाधिकारी कार्यालय, बीड यांचे प्रशासकिय मान्यता आदेश क्रमांक जिनिस्/ ०/ २०२१/ MAY/ AAO/००४५ दिनांक ३१.०५.२०२१  
२. जिल्हाधिकारी कार्यालय, बीड यांचे प्रशासकिय मान्यता आदेश क्रमांक जिनिस्/ ०/ २०२१/ Jun/ AAO/०००८५ दिनांक ०९.०६.२०२१  
३. शासन निर्णय क्रमांक यंत्रख - २०२२/ प्र.क्र.८६/ प्रशा-१ मंत्रालय, मुंबई दिनांक १६.०३.२०२२  
४. महाराष्ट्र शासन, वैद्यकीय शिक्षण व औषधीद्रव्ये विभाग, मुंबई यांचे पत्र क्रमांक जिवायो -२०२२/ प्र.क्र.५९/प्रशा -१ दिनांक १५.०३.२०२२  
५. जिल्हाधिकारी तथा सदस्य सचिव, जिल्हा नियोजन समिती, बीड यांचे पत्र क्रमांक जिनीस/ जिवायो/ पुनर्वि/ २१-२२/ १९४० दिनांक १७.०३.२०२२

या रुग्णालयास आवश्यक असलेल्या खालील साहित्याची खरेदी संदर्भित आदेशाच्या अधिन राहून करावयाची असल्याने खालील साहित्याचे दर पत्रके विहित नमुन्यात या कार्यालयास सादर करण्यात यावेत.

अ.क्र.	साहित्याचे नांव	संख्या
१.	Hospital Beds Fowler	१
२	Hospital Beds Semi Fowler	१
३	Hospital beds semi fowler with side railings	१
४	ICU Beds Manual	१
५	Multipara Monitor NIBP and ECG	१
६	Vital Signs Monitors	१
७	Stretcher	१
८	Stretchers with IV stand	१
९	Patient Trolley	१
१०	Pharmaceutical Fridges ५०० Ltr.	१
लॉन्डी युनिटी		
८	(A) GEW 90 WASHING MACHINE INNER & OUTER DRUM OF STAINLESS STEEL SHEETS. MACHINE COMPLETE WITH 3 H.P. 3 PHASE ELECTRIC MOTOR AND	१



	AUTOMATIC SELF REVERSING STARTER.	9
	(B) GEW 40 HYDRO EXTRACTOR INNER BASKET & OUTER DRUM MADE OF STAINLESS STEEL SHEETS. MACHINE COMPLETE WITH 5 H.P. 3 PHASE ELECTRIC MOTOR STARTER	9
	(C) GEW 60 DRYING TUMBLER ( ELECTRIC HEATED ) INNER DRUM MADE OF STAINLESS STEEL SHEETS. & OUTER DRUM MADE OF POWDER COATED MACHINE COMPLETE WITH 2 H.P. SUCTION BLOWER. 2 H.P. 3 PHASE ELECTRIC MOTOR 36KW HEATERS & CONTROL PANEL	9
	(D) GEW 4016 ELECTRICALLY HEATED ROLL PRESS WITH 1 H.P. GEAR BOX. 12 KW HEATERS & AUTOMATIC CONTROL SYSTEM.	9
9	Mortuary cold Cabinet 4 body	9
90	Mortuary cold Cabinet 2 body	9
99	Mortuary cold Cabinet 1 body	9
92	Zerox Machine	9
93	Computer	9
98	All In one Printer	9
94	A scan with pachymeter	9
96	Centrifuge clinical (high End)	9
97	Chloroscope (High End)	9
98	Craft Water Testing Kit (High End)	9
99	Direct Ophthalmoscope	9
20	Ear Instrument Set (Medium Set)	9
29	Electro Surgical Unit ( Low End )	9
22	Evisceration set	9
23	First Aid Kit (High End)	9
28	Horrocks Water Testing Kit (High End)	9
24	Indirect ophthalmoscope	9
26	Kertometer	9
27	Meat cutting machine thin body section	9
28	Microtome sledge large cutting machine	9
29	Mosquito catching kit (High End)	9
30	Public Address System (Portable) (High End)	9
39	SOUND LEVEL METER (High End)	9

तसेच सदर सुचनेनुसार मोहरबंद दरपत्रके मा.अधिष्ठाता, स्वामी रामानंद तीर्थ ग्रामीण शासकीय वैद्यकीय महाविद्यालय व रुग्णालय अंबाजोगाई यांच्या नावे सादर करण्यात यावीत. तसेच सदरील साहित्यांचे दरपत्रक सादर करण्यासाठी अंतिम दिनांक 28/03/2022 रोजी दुपारी 4.00 वाजेपर्यंत असून प्राप्त झालेली दरपत्रके दिनांक 29/03/2022 रोजी प्रशासकीय

D:\E Drive\Desktop\Sarkate\Quotation.docx



यांलयात खरेदी समिती समक्ष उघडण्यात येतील. सार्वजनिक सुटीच्या दिवशीही मोहरबंध दरपत्रकाचा लिफाफा कार्यालयीन ठे नुसार स्विकारण्यात येईल.

### अटी व शर्ती

१. दरपत्रक धारकाने मुबई दुकाने व आस्थापना अधिनियम १९४८ नुसार दुकानाचे शासन मान्य नोंदणी प्रमाणपत्र छांयाकीत प्रत दरपत्रकासोबत जोडणे बंधनकारक आहे.
२. दरपत्रक धारकाकडे सुक्ष्म, लघु व मध्यम उद्योगक मंत्रालय भारत सरकार यांच्याकडे नोंदणी केलेले उद्योग आधार प्रमाणपत्र असल्यास प्राधान्य देण्यात येईल.
३. दरपत्र धारकाच्या दुकानाचे नाव, संपूर्ण पत्ता, नोंदणी क्रमांक, जीएसटीनंबर व पॅन नंबर असलेल्या दुकानाच्या लेटर पॅडवर सही व शिक्का असलेली दरपत्रके सदर साहित्याच्या अ. क्रमांक यादीनुसार सादर करण्यात यावी, तसेच ज्या साहित्यांचे दर उपलब्ध होऊ शकत नाहीत त्या साहित्याच्या दराच्या ठिकाणी एन. ए. (NA) नमुद करावे. दरपत्रका सोबत शासन मान्य जीएसटी प्रमाणपत्र, फर्मच्या नावाचे किंवा प्रोप्रायटरच्या नावाचे पॅन कार्डची छांयाकीत प्रत तसेच एकल दरपत्रक धारक असल्याचे स्वतः स्वाक्षरीचे प्रमाणपत्र जोडणे बंधनकारक आहे. सदर प्रमाणपत्र नमुना देण्यात आलेला आहे.
४. दरपत्रकातील साहित्यांचे दर शासन नियमानुसार सर्व करांसहीत बाजार भावापेक्षा जास्त दराचे सादर करण्यात येऊ नये. तसेच सर्व साहित्य स्वतः स्वखर्चाने दहा दिवसांच्या आत पुरवठा करणे बंधनकारक राहिल. तसेच वाहतुक खर्च किंवा इतर कोणताही जादा खर्च देण्यात येणार नाही.
५. मागविण्यात आलेल्या साहित्यांचे दरपत्रक प्रमाणित झाल्याच्या दिनांकापासुन सहा (०६) महिन्यापर्यंत वैध राहतील.
६. प्रशासकीय कारणास्तव देयके अदा करण्यास विलंब झाल्यास विलंब शुल्क किंवा व्याज देण्यात येणार नाही.
७. पुरवठा करण्यात येणारे साहित्य वैध कालावधीचे व चांगल्या प्रतीचे असावे. हलके किंवा निकृष्ट दर्जाचे असल्यास पुरवठा आदेश रद्द करण्यात येतील व त्याची सर्वस्वी जबाबदारी आपणावर राहिल.
८. तसेच अपूर्ण माहितीसह व प्रमाणपत्रा शिवाय सादर केलेली संबंधितांची दरपत्रके विना स्पष्टीरण नाकारण्यात येतील तसेच प्रशासकिय कारणास्तव किंवा निधी अभावी काही अडचण निर्माण झाल्यास साहित्य खरेदी बाबत सदरच्या दरपत्रकाची संपूर्ण प्रक्रिया रद्द करण्याचा अधिकारी अधिष्ठाता यांना राहिल.
९. उपरोक्त प्रमाणे अटी व शर्ती मान्य असल्यासच सदरचे दरपत्रके सादर करावे.
१०. सदर खरेदी प्रक्रिया जिल्हाधिकारी कार्यालय, बीड यांचेकडुन प्रशासकिय मान्यता मिळण्याच्या व निधी मिळण्याच्या अधिन राहुन राबविण्यात येत आहे. प्रशासकिय मान्यता अभावी अथवा निधीच्या अभावीद दरपत्रके मागविण्यात आलेल्या साहित्याची खरेदी प्रक्रिया कोणतेही कारण न देता स्थगित ठेवणे अथवा खरेदी प्रक्रिया रद्द करण्याचे अधिकारी अधिष्ठाता स्वामी रामानंद तिर्थ ग्रामीण शासकिय वैद्यकिय महाविद्यालय व रुग्णालय, अंबाजोगाई यांना राहतील. या बाबत आपणास कोणत्याही प्रकारची तक्रार करण्याचा अधिकार राहणार नाही.

  
अधिष्ठाता,

स्वामी रामानंद तिर्थ ग्रामीण शासकिय  
वैद्यकिय महाविद्यालय व रुग्णालय, अंबाजोगाई

प्रत

प्रत :-


D:\E Drive\Desktop\Sarkate\Quotation.docx



## Annexure-X

### Specification for Motorised ICU Bed

- A. Overall Size: Approx 2290mm X 1065mm (90"X42") (Buffer to Buffer)
- B. Bed Platform frame size 2230mm x 990mm, 88.8"x39"
- C. The Fully motorized Bed allows the Trendlenburg positions, Reverse Trendlenburg positions, Lateral tilt left, Lateral tilt right, Knee rest position, Back rest positions and Height adjustment controlled through the corresponding electro-mechanical actuators and it is adjusted by soft touch hand operator wired remote control system and has noiseless operations and also has the facility to adjust all the same positions by Nursing Control Panel at foot end.
- D. Roto-translating Back and foot end where in back rest section moves back as it goes up preventing the patient from being pushed downwards as in traditional bens simultaneously even the food end moves away from the center of the bed so that the patient is more comfortable.
- E. Base frame mainly made made of 50 x 25 x 2mm (14 G) and 60mm x 30mm x 1.6 (16G) ERW tubes and MS flats size 6mm thick for various supporting links
- F. The bed works on 3 synchronized vertical column system.
- G. The height adjustment without mattress from 495mm to 890mm
- H. All movements are controlled via wired remote control system as well as nurse control system, with digital display on ACP & Embedded Panels on Middle Railing.
- I. The Motorized Bed top is divided into four fix sections: Head Section, Trunk Section (Back section), Trunk section (lumber section), and leg section.
- J. The Motorized Bed four fix sections top is made up of 18 G CRCA sheet double press bend and uniformly embossed holes from 23 mm diameter can also be provided with ABS top.
- K. The Trendlenburg position is form rest position to 14 degree and reverses Trendlenburg position is from 14 degree rest position.
- L. Easily readable from the indicator provided on railings, Digital Display on ACP
- M. The Motorized Bed Knee frame is made up of 18 GCRCA sheet and welded to 25 mm x 5 mm thick flat section.
- N. The four section frame is made from 30 mm x 30 mm Square ERW tube.
- A. The knee position is from rest position to 30 degree and reverse to the rest position.
- B. The Backrest position is from rest position to 75 degree and reverse at rest position easily readable from the indicator provided on railings
- C. The lateral tilt position should be at least 18 ° on each side.
- D. The Motorized Bed has polymer molded Split type railings to cover full bed length.





- E. Polymer rails are fitted to the back rest and foot and flap and move along with the flaps when positioned. Thus providing maximum safety to the patient. Care should be taken that these rails are not installed to the bottom bed frame.
- F. The Motorized Bed has a telescopic detachable height adjustable 4 pole IV rod to mount syringe pumps. There should be four locations on the bed to mount this IV rod.
- G. The Motorized Bed has mobile base with four numbers 125 mm diameter heavy duty non rusting castors with polyurethane tires for longitudinal and lateral movement with smooth and easy central and directional locking arrangement so that the staff can easily handle the movements and the locking of the bed.
- H. Head & Foot board should be made of blow molded poly propylene. Head board and foot board should be with inserts to mount it on bed frame. Removable PP head board and foot board should have cutouts, for better gripping. The board should have provision to paste provision to paste color stickers.
- I. The Motorized Bed has manual quick release mechanism on either side for back page 20 of 22 section adjustment during emergency situation.
- J. Quick release mechanism on either side of the bed. K. CPR position can also be sought electronically.
- K. Simultaneous Electronical adjustment of backrest and knee rest on ACP and Embedded panel. One touch Key for 'Emergency head Down' on the ACP and outside Embedded panel. Digital degree display through ACP for backrest, knee rest, trendelenburg / Reverse trendelenburg, Lateral tilt and Cardiac chair potions.
- L. The weight of patient will be displayed on ACP with help of Load cells mounted in base frame.
- M. Safety alarm such as Railing down, if middle railing is kept down. Patient out of bed Alarm if patient moves out of bed. Nurse assistance call facility provided with ACP and embedded panel.
- N. All electro mechanical actuators need to be compatible with class of IP 54/IP 66. Bed should have ISO 60601-2-52 certificate for patient safety.
- O. Patient load Bearing Capacity – 240kgs, Four corner rubber buffers of 100MM diam.
- P. Premium single section mattress with 6" thick wave shape on both sides, high quality, high density, flame retardant from with cover fabric beige coloured, flame retardant, antibacterial.
- Bed should have 200mm Extension from Leg end & Mattress for Bed Extension.
- Q. Premium single section mattress with 6 inch thick ICU foam mattress
- R. X. High density, flame retardant foam with cover fabric beige colored antibacterial.






Name of Instrument: Hospital Bed  
Technical specification

Patient Bed / Hospital Bed.

Specifications:	
Model Number	GENERAL SEMI FOWLER LITE WITH MATTRESS ONLY
Type	Manual
Material	Iron
Elevation Present	Yes
Adjustable Height	No
Side Rails Present	No
Wheels Present	No
Battery Back-up Present	No
Adjustments Available	BACK REST, FOOT REST
Sleep Surface	85*100*200
Maximum Weight Capacity	200 kg
Width	95 cm
Height	100 cm
Length	200 cm
Weight	20 kg


  
Professor & Head  
DEPT. OF ANAESTHESIA,  
S.R.T.R. Govt. M.C.H. AMBAJOGAI



Name of Instrument: ICU Bed  
Technical specification

ICU Bed

Specifications:	
Type	Manual
Material	Iron
Elevation Present	Yes
Adjustable Height	Yes
Wheels Present	Yes
Adjustments Available	Head rest and Leg rest
Maximum Weight Capacity	100 kg
Width	88.9 cm
Height	58.42 cm
Length	203 cm
Weight	20 kg


  
Professor & Head  
DEPT. OF ANAESTHESIA,  
S.R.T.R.Govt.M.C.H.AMBAJOGAI



Name of Instrument: stretcher  
Technical specification

Patient Stretcher

Specifications	
Model Number	HOSPITAL Patient Stretcher Trolley(MS)
Material	Steel
Foldable	No
Wheeled	Yes
Maximum Load Capacity	150 kg
Width	56 cm
Height	81 cm
Depth	210 cm

  
Professor & Head  
DEPT. OF ANAESTHESIA,  
S.R.T.R.Govt.M.C.H.AMBAJOGAI



Name of Instrument: Patient Trolley / Emergency Trolley  
Technical specification

### Emergency Trolley

#### Silent Features of Emergency medicine trolley

- Cardiac massage board laminated shelves.
- 2 Plastic Cabinet with 3 drawers in each.
- 12.5cm swivel media castors, two are breaking.
- Provision for Corner buffers and I.V. Rod.
- Oxygen Cylinder Holder provision.
- Six removable bins & two Polystyrene storage unit with three drawers each.
- Size : 94L x 49W x 153H Cm.

  
Professor & Head  
DEPT. OF ANAESTHESIA,  
S.R.T.R. Govt. M.C.H. AMBAJOGAI



Name of Instrument: Pharmaceutical Freeze  
Technical specification.

**Pharmaceutical Freeze:**

**General**

Brand	Blue Star
Model Number	CHFDD500MGPW
Color	White, Blue
Capacity	484 L
Defrost Type	Manual
Lid Type	Metal Top
Door Type	Swing Door
Number of Compartments	1
Lock Present	Yes
Inbuilt Lighting	No
Defrost Water Drain Present	Yes

**Power Features**


Power Requirement	AC 230 V, 50 Hz
Power Consumption	4.17

**Additional Features**

Cyclopentane Insulation

**Dimensions**

Width	164 cm
Height	83.5 cm
Depth	67 cm
Weight	68 kg

  
**Professor & Head**  
DEPT. OF ANAESTHESIA,  
S.R.T.R. Govt. M.C.H. AMBAJOGAI



# Specification for purchase of Instrument in Dept of

Medicine

Date: 19/03/2022

## ICU BED

Operating with 4 Nos. of actuators with remote control one control unit with battery back up One actuator for height adjustment second actuator for tilting bed third for head up position panel fourth actuator for knee bed panel leg panel adjustable on ratchet bar fiber bows & head & foot Bows) heavy duty plastic collapsible side reeking heavy duty 5 nylon wheels with two no of break wheel

## ICU MANUAL BED

MS top frame with 3 section having Ms performed top panels 4 motion viz. H-low Trendelenburg/Reverse Trendelenburg backrest & knee rest operated by screw IV Rod 5 wheel set with 2 breakable wheels PVC ( fiber ) made patient guard rail sliding up/down Easily removable fiber bow IV rod provision at 2 locations urine bag tool at 2 location

  
प्रो. रा. ती. ग. रा. व. म. त. रु. अबाजोगाई  
औषधवैद्यकशास्त्र विभाग  
**Professor & HOD**  
Dept. Of Medicine  
S.R.T.R.G.M.C Ambajogal

UOM of Ambajogal  
Ambajogal  
S.R.T.R.G.M.C Ambajogal



# Specification for purchase of Instrument in Dept of

Medicine


Date: 19/03/2022

## FOWLER BED

Top frame with 3 sections Panels with steel sheet or ecotin sheet top 2 separate screws for maneuvering propped up backrest & knee rest Provision to fit patient guard rail Easily removable bows Tubular legs with nylon shoes IV Rod provision at 2 locations

## Semi Fowler Bed

Top frame with 2 sections Panels with steel sheet top screws for maneuvering propped up backrest & leg rest provision to fit patient guard rail Easily removable bows Tubular legs with nylon shoes IV Rod provision at 2 location.

for 

प्राध्यापक व विभागप्रमुख

औषधवैद्यकशास्त्र विभाग  
**Professor & HOD**

स्वा.रा.ती. प्रशा. वै. मे. वि. अंबाजोगाई  
**S.R.T.R.G.M.C Ambajogal**




## Specification for purchase of Instrument in Dept of

# Medicine

**Date: 19/03/2022**

## Streture Trolley

Ms Powder coated Tubular frame mounted in 8'' diameter rods. Heavy castors Detachable steel sheet stretcher Top

for   
 प्राध्यापक व विभागप्रमुख  
 Professor & HOD  
 चैतन्य वैद्यकशास्त्र विभाग  
 Dept. Of Medicine  
 स्वा.रा.डी.आर.एम.एम्.बा.जोगाई



# Specification for pharmaceutical refrigerator

## Product Specification

Usage/Application	Pharmaceutical Freezers
Material	Type 304 stainless steel
Shape	Square
Capacity	500L
Temperature Range	50 DegreeC to -180 DegreeC
Automation Type	Automatic
Color	Any
Phase	Any
Operating Voltage	230V
Minimum Order Quantity	1

## Product Description

### Easy Programming and Monitoring:

- Chamber and sample temperatures and operation status simultaneously display on backlit LCD.
- Pre-Cool step automatically begins temperature ramp when chamber and sample temperatures are equilibrated within 1°C.
- Audible indicators alert operator when hold time has elapsed.
- Operation continues if power outage lasts less than 10 seconds; audible/visual alarm sounds if outages last longer than 10 seconds.
- Modifiable access code offers added security.

### LN2 Freezing System Components:

- Intuitive control panel and integrated thermal printer
- Dual solenoid valves that increase LN2 injection volume for precise temperature control and accelerated freezing for optimum cell viability
- Overtemperature protection on heating element

### Construction:

- Type 304 stainless steel
- Exterior powder-coat finish
- Foamed in-place polyurethane insulation

*Paul p*  
10.3.2022  
*pm*



## Specification for purchase of Instrument in

Casualty


Date: 19/03/2022

### FOWLER BED

Top frame with 3 sections Panels with steel sheet or ecolin sheet top 2 separate screws for maneuvering propped up backrest & knee rest Provision to fit patient guard rail Easily removable bows Tubular legs with nylon shoes IV Rod provision at 2 locations

### Semi Fowler Bed

Top frame with 2 sections Panels with steel sheet top screws for maneuvering propped up backrest & leg rest provision to fit patient guard rail Easily removable bows Tubular legs with nylon shoes IV Rod provision at 2 location.



वैद्यकिय अधिक्षक

स्वा.रा.ती.ग्रा.शा.वै.म. व रु.,अंबाजोगाई



# Specification for purchase of Instrument in

Specific

Casualty

Date: 19/03/2022

## ICU BED

Operating with 4 Nos. of actuators with remote control one control unit with battery back up One actuator for height adjustment second actuator for tilting bed third for head up position panel fourth actuator for knee bed panel leg panel adjustable on ratchet bar fiber bows & head & foot Bows) heavy duty plastic collapsible side reeking heavy duty 5 nylon wheels with two no of break wheel

## ICU MANUAL BED

MS top frame with 3 section having Ms performed top panels 4 motion viz. H-low Trendelenburg/Reverse Trendelenburg backrest & knee rest operated by screw IV Rod 5 wheel set with 2 breakable wheels PVC ( fiber ) made patient guard rail sliding up/down Easily removable fiber bow IV rod provision at 2 locations urine bag tool at 2 location

*Bode*

वैद्यकिय अधिक्षक

स्वा.रा.ती.ग्रा.शा.वै.म. व रु.,अंबाजोगाई



03/2022


## Specification for purchase of Instrument in

Casualty

Date: 19/03/2022

### Streture Trolley

Ms Powder coated Tubular frame mounted in 8'' diameter rods. Heavy castors Detachable steel sheet stretcher Top

  
७ वैद्यकिय अधिक्षक  
स्वा.रा.ती.ग्रा.शा.वै.म. व रु.,अंबाजोगाई

	System Control Input Devices : USB keyboard,mouse and foot pedal	
A scan with pachymete r	<b>ASCAN PROBE</b>	
	Probe Frequency	10MHz
	Fixation	Internal LED
	<b>Measurement range</b>	
	Axial Length	14.0 mm to 40.0mm
	ACD	2.0 mm to 6.0 mm
	Lens Thickness	2.0 mm to 7.5mm
	Measurement Accuracy	+ 0.1 mm
	<b>Measurement Techniques</b>	
	Method	Immersion / Contact
	Mode	Auto / Manual
	Lens Type	Aphakic, Normal, Cataract, Dense Cataract, Pseudophakia ( Silicone, PMMA, Others ) Silicone Oil
	<b>IOL Calculation</b>	
	Formulae	SRK - T, SRK - II, Holladay, Binkhorst, Hoffer-Q, F, AME* and Post Refraction Formulae
	Display Control	High resolution 8 inch colour display With Touch screen
	Storage	100 Patient records, 10 preset users 25 IOL Configurations
	Camp Mode	Fast measurement with IOL calculation In single screen
	Printer	Printer Fast Thermal printer with Auto Cutter
	<b>Power</b>	
	Electrical Requirements	230V AC / 50Hz
	<b>PACHYMETER Specifications :( General )</b>	
	Measurement Range	200- 10



		00 Microns
	Accuracy	+ Or- 4 Microns
	Frequency	20MHz
	Communication	RS232 for PC connection
	<p>IOP Adjust Software</p> <ul style="list-style-type: none"> <li>• Easily Adjust IOP based on measured CCT.</li> <li>• CCT measurements</li> <li>• Guaranteed fast and easy Measurements</li> </ul> <p>Scan Modes</p> <ul style="list-style-type: none"> <li>• Continuous/Mapping</li> <li>• User programmable Mapping (up to 90 maps)</li> </ul> <p>Measurements</p> <ul style="list-style-type: none"> <li>• Adjustable Corneal Velocity</li> <li>• Automatic Sensing Algorithm</li> <li>• Measurement Review</li> <li>• 900 Scan Average with Standard Deviation</li> </ul> <p>Probe</p> <ul style="list-style-type: none"> <li>• 20MHz Angled or Straight</li> </ul> <p>Other Features</p> <ul style="list-style-type: none"> <li>• Auto /Manual Gain</li> <li>• Automatic calculation of standard deviation and average axial Length (Serial of 90 measurement )</li> <li>• Simultaneous display of 3 different IOL calculation</li> <li>• RTC shown the Date Time throughout the life of the instrument.</li> <li>• Various user Programmable Printouts format</li> <li>• Measurement possible for various velocity of each segment.</li> <li>• *AME Formula -The new generation programmed software Takes care of any Axial Length.</li> <li>• CE of country of origin and/or US FDA and/or European CE</li> </ul>	

### Centrifuge clinical

Electrical operated dome type sturdy stable heavy body with resiliently mounted motor working on 220V AC 50 Hz single phase for vibration free performance with built in 5- speed regulator and non-removable swing out rotor. Complete with tube carriers. Maximum speed 3500 RPM. neatly finished in stoving enamel.

- a) 8 x 15 ml tubes.



## **Chloroscope**

it is used to check the residual chlorine in drinking water, Simple, Sturdy and Portable apparatus.

## **Craft Water Testing Kit/MICROPROCESSOR WATER AND SOIL ANALYSIS KIT**

16X2 Alphanumeric LCD Display covering 6 parameter pH, Conductivity, Temperature, TDS, ORP and salinity battery cum mains operated, completer with accessories, fitted in briefcase. RS 232 Computer interface facility available



## Direct Ophthalmoscope

<p>8 Direct Ophthalmoscope</p>	<ul style="list-style-type: none"> <li>• Unique optical system. It should optimize the Gullstrand principle with aspherical optics (separation of illumination and observation beam). Corneal and iris reflexes are eliminated. A full view is guaranteed even with small pupils.</li> <li>• XHL Xenon Halogen Technology. Bright, white light.</li> <li>• Range of lenses: 27 lenses from -35 D to +40 D.</li> </ul> <p>+ in 1 D steps: 1 – 10 15 20 40 D</p> <p>– in 1 D steps: 1 – 10 15 20 25 35 D</p> <ul style="list-style-type: none"> <li>• 7 apertures with separate red-free filter. Suitable for large or small pupils. Incorporates slit aperture, fixation star, cobalt blue filter and red-free filter for improved contrast.</li> <li>• Recessed, multi-coated viewing window. Avoids stray light.</li> <li>• Dustproof housing. Maintenance-free.</li> <li>• Optics mounted on precision metal chassis. Durable, precise.</li> <li>• Ergonomic shape.</li> </ul> <ul style="list-style-type: none"> <li>• Spare Parts :- 2 Additional Bulb</li> <li>• Power Requirement :- 220 to 240V</li> <li>• Frequency:- 50Hz</li> <li>• Internal Batteries:- Rechargeable / Compatible 2.5V &amp; 3.5V Batteries</li> <li>• LED display to indicate changing stapes :- Handles Provided</li> </ul> <p>Soft orbital support. Protects the users' glasses and steadies the instrument</p>
--------------------------------	---



## EAR INSTRUMENTS SET(MEDIUM END)

Clinical purpose	<ul style="list-style-type: none"><li>• OPD Procedures</li><li>• Ear surgeries-<ol style="list-style-type: none"><li>1. Tympanoplasty</li><li>2. Mastoidectomy</li><li>3. Stapedectomy</li></ol></li></ul>													
Used by clinical department/ward	ENT Department													
SPECIFICATIONS	<p><b>– COST – APPROX. INR. 1-1.5 LAKHS</b></p> <p><b>SPECIFICATIONS:</b></p> <ul style="list-style-type: none"><li>• Instruments should be made of high-grade stainless steel. The quality of steel should comply with the DIN, US-FDA, or European CE, issued by TUV</li><li>• Instruments should be of high quality and precision.</li><li>• Instruments should be light weight, strong and durable</li><li>• Instruments should be non-magnetic</li><li>• Instruments should be autoclavable at 134 deg C and follow international US-FDA and EN ISO norms for sterilization</li></ul> <p><b>INSTRUMENTS-</b></p> <table><tr><td>1. Fcps., Artery. Mixer. Rt.Ald. Fine.15cm/6".</td></tr><tr><td>2. Fcps., Crocodile. Serr. .8mm/4mm. Jaws.Str. 8cm.</td></tr><tr><td>3. Freer Elevator. D/E. 4mm. Sh/Bl. 19cm/7.5".</td></tr><tr><td>4. Metzenbaum Scissors, Cvd. 15cm/6".</td></tr><tr><td>5. Elevator, Farabeuf. 8mm. Cvd. 15cm/6".</td></tr><tr><td>6. Cannula, Verhoeven. 2.6mm/12G. Luer. 7.5cm.</td></tr><tr><td>7. Cannula, Verhoeven. 2mm/14G. Luer. 7.5cm.</td></tr><tr><td>8. Cannula, Verhoeven. 1.6mm/16G. Luer. 7.5cm.</td></tr><tr><td>9. Cannula, Verhoeven. 1.2mm/18G. Luer. 7.5cm.</td></tr><tr><td>10.Cannula, Verhoeven. 1.0mm/19G Luer. 7.5cm.</td></tr><tr><td>11.Cannula, Verhoeven. .8mm/21G. Luer. 7.5cm.</td></tr><tr><td>12.Cannula, Verhoeven. .7mm/22G. Luer. 7.5cm.</td></tr><tr><td>13.Cannula, Verhoeven. .5mm/24G. Luer. 7.5cm.</td></tr></table>	1. Fcps., Artery. Mixer. Rt.Ald. Fine.15cm/6".	2. Fcps., Crocodile. Serr. .8mm/4mm. Jaws.Str. 8cm.	3. Freer Elevator. D/E. 4mm. Sh/Bl. 19cm/7.5".	4. Metzenbaum Scissors, Cvd. 15cm/6".	5. Elevator, Farabeuf. 8mm. Cvd. 15cm/6".	6. Cannula, Verhoeven. 2.6mm/12G. Luer. 7.5cm.	7. Cannula, Verhoeven. 2mm/14G. Luer. 7.5cm.	8. Cannula, Verhoeven. 1.6mm/16G. Luer. 7.5cm.	9. Cannula, Verhoeven. 1.2mm/18G. Luer. 7.5cm.	10.Cannula, Verhoeven. 1.0mm/19G Luer. 7.5cm.	11.Cannula, Verhoeven. .8mm/21G. Luer. 7.5cm.	12.Cannula, Verhoeven. .7mm/22G. Luer. 7.5cm.	13.Cannula, Verhoeven. .5mm/24G. Luer. 7.5cm.
1. Fcps., Artery. Mixer. Rt.Ald. Fine.15cm/6".														
2. Fcps., Crocodile. Serr. .8mm/4mm. Jaws.Str. 8cm.														
3. Freer Elevator. D/E. 4mm. Sh/Bl. 19cm/7.5".														
4. Metzenbaum Scissors, Cvd. 15cm/6".														
5. Elevator, Farabeuf. 8mm. Cvd. 15cm/6".														
6. Cannula, Verhoeven. 2.6mm/12G. Luer. 7.5cm.														
7. Cannula, Verhoeven. 2mm/14G. Luer. 7.5cm.														
8. Cannula, Verhoeven. 1.6mm/16G. Luer. 7.5cm.														
9. Cannula, Verhoeven. 1.2mm/18G. Luer. 7.5cm.														
10.Cannula, Verhoeven. 1.0mm/19G Luer. 7.5cm.														
11.Cannula, Verhoeven. .8mm/21G. Luer. 7.5cm.														
12.Cannula, Verhoeven. .7mm/22G. Luer. 7.5cm.														
13.Cannula, Verhoeven. .5mm/24G. Luer. 7.5cm.														



	14.Fcps., Crocodile. Serr. .6mm/3.5mm. JawsStr. 8cm.
	15.Fcps., Crocodile Cup. 1mm/.9mm. Oval Jaw Str. 8cm.
	16.Fcps., Crocodile Cup. 1mm/.9mm. Oval Jaw Cvd.Rt. 8cm.
	17.Fcps., Crocodile Cup. 1mm/.9mm. Oval Jaw Cvd.Lt. 8cm.
	18.Scissors, Micro Ear. Str. 4mm. Blades. 8cm.
	19.Fcps., Wire Closing. Crocodile. .8x6mm Jaw. McGee. 8cm.
	20.Malleus Nipper, House-Dieter. Upward. 8cm.
	21.Fcps., Piston Holding. 6mm. Jaw. 8cm.
	22.Pick. Str., 16.5cm.
	23.Pick, Short-Cvd. 16.5cm.
	24.Pick, 1mm. 45°. 16cm.
	25.Pick, 0.5mm. 45°. 16cm.
	26.Pick, 0.5mm. 90°. 16cm.
	27.Pick, 1mm. 90°. 16cm.
	28.Round Knife.2.5mm. 45°. 16cm.
	29.Sickle Knife. 6mm.Cvd.16cm.
	30.Plester Flap Knife. Oval. Vertical. 2.5mmWx3.5mmL. 16cm.
	31.Round Knife with holes. 4mm. 16cm.
	32.Elevator, Austin-Duckbill. 16cm.
	33.Ball Probe, Goldman. 0.8mm. 45°. 16cm.
	34.Piston Depth Gauge. Fisch. 16.5cm.
	35.Curette, House. Ald. 2mm/2.5mm. Length15cm.
	36.Curette, House. Ald. 1.5mm/2mm. Length15cm.
	37.Fcps., Vein Graft Press. King. ø20mm Jaw 15cm.
	38.Adaptor, Fisch with cut-off. Luer. 8cm
	39.Shea/Farrior Ear Speculum. Set of 4. Oblique ends. 4mm/5mm/6mm/7mm. Black. 41mm.
	40.TumarkinTransmeatal Specula. Set of 4. 4mm/5mm/6mm/7mm. 45mm.
	41.Suction Cannula. Frazier/Lempert. Set of 4. 1mm-4mm. Length 19cm/7.5".
	42.Retraction, Plester. 2x2/18mm approximating Prongs. Cvd. 11cm/4.25".



	43. Retractor, Plester. 2 Prong X Right-Solid blade. 11cm/4.5".
	44. Retractor, Plester. 2 Prong X Left-Solid blades. 11cm/4.5".
	45. Retractor, Weitlaner. 2x3 Prong-Sp/Bl. Cvd. 13cm/5.25".
	46. Retractor, Weitlaner-Wullstein. 3x3 Prong-Shp. Cvd. 13cm/5.25".
	47. Retractor, Mollison. 4x4 Prong-Sp. Cvd. 16cm/6.25".
	48. Teflon Piston Cutting Jig.
	49. Teflon Piston Autoclaving Box.
	50. Sterilisation Box, for Autoclaving; Std. Stainless Steel. Size 35cmX12X7.5cm/14"x5"x3".
	51. Kalelker/Fisch Perforator. 0.3mm.
	52. Kalelker/Fisch Perforator. 0.4mm.
	53. Kalelker/Fisch Perforator. 0.5mm.
	54. Kalelker/Fisch Perforator. 0.8mm.



## **ELECTRO SURGICAL UNIT (Low End)**

**Approx. Cost Rs.3,00,000/-**

### **TECHNICAL SPECIFICATION**

- It should be a Microprocessor control based Generator
- 400 Watts (390 kHz)
- Minimum 12 modes of cutting and 4 modes of coagulation
- Should have 4 modes of bipolar including Bipolar, Micro, Macro and Bipolar cut.
- Should have 4 modes of Ecut
- Possible to do Monopolar and Bipolar Turp Cases (underwater cutting)
- Three independent display to show cut, coagulation and bipolar power levels
- Automatic recognition of patient plate (single / split)
- Patient plate contact level monitoring
- Monopolar and Bipolar REMOTE function to adjust power levels using control accessories
- EZCut system automatically assists initial cut power levels.
- High cut function to provide a high efficiency cut with enhanced performance in low and high impedance tissues
- Compatible with Argon Plasma Coagulator
- Weight less than 6kgs
- Self-testing during the time of switching on

### Eviscerati on Set

33	Eviscerati on Set	<ol style="list-style-type: none"> <li>1. Adson fixation forceps</li> <li>2. Hartman mosquito forceps straight</li> <li>3. Colibri forceps 1 x 2 teeth 0.12mm</li> <li>4. Desmarres Lid retractor size 1-12mm width</li> <li>5. Enucleation scissors ring handle medium curve</li> <li>6. Enucleation scissors ring handle strong curve</li> <li>7. Knapp strabismus scissors blunt tips ring handle straight</li> <li>8. Knapp strabismus scissors blunt tips ring handle curved</li> </ol>
		<ol style="list-style-type: none"> <li>9. Lancaster eye speculum</li> <li>10. Wells enucleation spoon small</li> <li>11. Bunge evisceration spoon small</li> <li>12. Bunge evisceration spoon large</li> <li>13. Sterilization box with silicone mat</li> </ol>



## First Aid Kit

Crepe Bandage 6cm, Adhesive bandage regular  
Pain Relief Gel 30gm, Povidone Iodine Ointment 20gm  
Oral Clinical Thermometer Medium, Antiseptic Liquid 50ml  
Absorbent Cotton I.P. 15gm, Microporous Surgical tape  
Paracip/Para choice, Roller Gauze 7.5cm\*4mtrs  
A pair of Scissors (Small)

## Horrocks Water Testing Kit

Alkalinity: 25 to 750 mg/l

Total Hardness : 25 To 1000 Mg/l, Chloride : 100 Mg/l



## Indirect ophthalmoscope

10	<p>Indirect ophthalmoscope</p> <ul style="list-style-type: none"> <li>• Indirect with Inbuilt Filters – Red Free, Cobalt Blue, Yellow</li> <li>• Camera With 5 Megapixel Resolution</li> <li>• Integrated Focus Adjustment</li> <li>• Suitable For The Examination Of Premature Babies</li> <li>• Interface And Software</li> <li>• Plug Into Any Laptop Or Computer Via USB 2.0 Interface</li> <li>• Software Program For Video Recording And Image Capture</li> <li>• Integrated Camera Design</li> <li>• Cable-Free Power Source System With mPack UNPLUGGED</li> </ul> <p>Rechargeable Battery Teaching aids, warranty for 3years. Including all spears and calibration work.</p>
	<p>Mandatory Accessories:-</p> <p>Three Pencils fundus chart scleral deperson, 20D condensing lens with anti-reflective waiting.</p> <p>Bulb:- 2nos, bulb holder, bulb cover.</p>

## Keratometer

	Radius of Curvature	5.0~10.2mm (Increments: 0.01mm)
	Corneal Power	33.00~67.50D (When Cornea Equivalent Refractive index is 1.3375. Increments selectable From 0.12, 0.25D)
	Corneal Astigmatism	0.00~-15.00D (Increments Selectable from 0.12,0.25D)
	Axis (AX)	1-180 (increments 1)
	Cornea equivalent Refractive index 1.3375	1.3375
	Measurement range	Ø2.0mm
	Contact lens base curve measurement	
	PD measurement	2.0~12.0mm (Increments:0.1mm)
	User Key	LCD monitor Down side



Specifications  
Meat cutting Machine  
(Medium End)

Stainless Steel Meat Cutting Machine, 2 hp motor,  
Table made of thick SS sheet with special heavy axles for easy and  
firm movement Machine should be supplied complete with one blade,  
starter, cord and plug Machine should work on 220V, Copper Winded  
Motor single phase, 50 Hz AC supply Machine should be fitted with  
moving table and extension table mounted on four ball bearing rollers  
Additional accessories

Blade – SS 310, Thickness of Blade = 0.5 MM

Size of cutting table 55x55x92 cm

Power= 750 Watt

Saw Length= 1650 mm

Saw Width= 19 mm

## Specifications

Microtome sledge large cutting

(Medium End)

Cutting stroke – 200-250 mm

Total feed range- +/- 8 degree horizontal and vertical

Specimen orientation - +/- 8 degree horizontal and vertical

Section thickness range 0-0.4  $\mu\text{m}$  in 1  $\mu\text{m}$  increments

Maximum specimen size 50X 50 mm.



## **Mosquito catching kit**

Product type: Mosquito and Insects trap.

Insect display box, sweep net, insects spreading board, entomology pins, Forceps, Lens, Killing Jar and Ethyl acetate.

### **Public Address System (Portable) :**

- 1 Speaker and 7.2A.H Rechargeable battery,
- 2) One Hand Mike
- 3) One Antina Cable,
- 4) One A.C Lead(Main cord) 5 METERS,
- 5) One Remote Control,



## **SOUND LEVEL METER (NOISE LEVEL METER) :**

Sound pressure accuracy:  $\pm 1.5$  dB (sound pressure standard, 94dB @ 1 KHz) Sound pressure frequency response: 30Hz-8KHz Dynamic range of sound pressure: 50 dB (for each measurement gear level) Technical specification of the sound level meter PCE-353

Measuring range 30 ... 130 dB

Resolution 0.1 dB Accuracy  $\pm 1$  dB

Measurement memory 30 measurements

Frequency 31.5 Hz ... 8 kHz

Measurement functions Leq, Lp, Ln Other features Peak-Hold, limit function

Manufacturer warranty 24 months PC-Software optionally available

Power supply 4 x 1.5 V AAA Interface RS-232

Dimension 236 x 63 x 26 mm

Weight 170 g

Delivery Contents of the sound level meter PCE-353 1 x sound level meter PCE-353, 1 x wind noise suppressor (foam ball), 1 x tool box, user manual

ॐ

## Specification for purchase of Instrument in Casualty

(A)

WASHING MACHINE

INNER & OUTER DRUM OF STAINLESS STEEL SHEETS. MACHINE COMPLETE WITH 3 H.P. 3 PHASE ELECTRIC MOTOR AND AUTOMATIC SELF REVERSING STARTER.

(B)

HYDRO EXTRACTOR

INNER BASKET & OUTER DRUM MADE OF STAINLESS STEEL SHEETS. MACHINE COMPLETE WITH 5 H.P. 3 PHASE ELECTRIC MOTOR STARTER

(C)


DRYING TUMBLER ( ELECTRIC HEATED )

INNER DRUM MADE OF STAINLESS STEEL SHEETS. & OUTER DRUM MADE OF POWDER COATED MACHINE COMPLETE WITH 2 H.P. SUCTION BLOWER. 2 H.P. 3 PHASE ELECTRIC MOTOR 36KW HEATERS & CONTROL PANEL

(D)

ELECTRICALLY HEATED ROLL PRESS

WITH 1 H.P. GEAR BOX. 12 KW HEATERS & AUTOMATIC CONTROL SYSTEM.

  
वैद्यकिय अधिक्षक  
स्वा.रा.ती.ग्रा.शा.वै.म. व रु., अंबाजोगाई



Sold by: **OEM**

OEM verified catalogue

[VIEW SELLER DETAILS](#)

★★★★★ 3.89

Refrigeration System- Unitary : RTU-10  
Type

Number of bodies : 4

Body Material : 304 Stainless Steel

Separate doors and handles : Yes  
for each chamber

Refrigerant Gas : R134A

Temperature Display : LED

Insulation Thickness : 80 millimeter  
[VIEW MORE](#)

*Product Power  
Asse prof-2 Power*

Location And Standard

GeMmy  
VARE  
CE  
PRODUCT HISTORY ①

Conformity to Electrical Safety Standard IEC 60601-1

Manufacturer should be ISO certified Yes

Construction

Door Material Stainless Steel

Refrigeration System- Unitary Type RTU-10

Number of bodies 4

Trolley Material Stainless steel

Body Material 304 Stainless Steel

Technical Specification

Integral Temperature Gauge Yes

Electronic temperature indicator cum controller Yes

Handles for Yes



Ask Gemmy

PRODUCT COMPARE PRODUCT HISTORY 1



Refrigerant Gas	R134A
Temperature Display	LED
Temperature of Mortuary Cabinet(degree celsius)	2 degC to 6 degC
Internal Lighting	Vapor proof incandescent lamp
Insulation Thickness	80 millimeter
Locking System	Standard Key Locks
Trolley sliding on telescopic rails	No
Defrosting Type	Automatic
Safety alarm	Audio, Visual
Insulation between the walls	High Grade Polyurethane
Type Of Alarm	Temperature Variation Alarm, Safety Alarm, NA
Internal Drainage	Yes
Air Circulation	Forced Air Circulation

**Ask Gemmy**

PRODUCT COMPARE

PRODUCT HISTORY ①

Voltage, +/-10%	240 Volt
Phase	Single phase
Frequency	50 Hertz

Dimension & Size	
Height	1422 millimeter
Width	1693 millimeter
Height With Cooling Unit And Pcc Platform	1422 millimeter
Depth	2420 millimeter

Accessories	
Optional Accessories	Stainless Steel tray, Stabilizer, User manual, Telescopic Carriage Tray

Warranty	5 year
----------	--------



Ask GEMmy

PRODUCT CATEGORY

PRODUCT HISTORY



Additional Parameter

Features

Trolley run on rollers fitted with ball bearings,Solid insulated doors,Removable Racks

Compressor is ISI Marked and CFC Free

Yes

Provision for simplified cadaver handling with maintenance of Hygiene

Yes

Test Report

Test Report Date and Numbers  
(Please write NA if not applicable)

NA

Test Report To Be Submitted To The Buyer On Demand

NA

Availability of Test Report from Central Govt/NABL/ILAC accredited lab to prove conformity to specification

No

Name and Address of the lab  
(Please write NA if not applicable)

NA



Ask GeMmy

PRODUCT COMPARE

PRODUCT HISTORY

①

Buy PSAW Stainless Steel Single phase Mortuary Cabinet, Warranty 2 year online | GeM

Country Of Origin: India  
Local Content (MII): 100%

Sold by: **OEM**

OEM verified catalogue

[VIEW SELLER DETAILS](#)

★★★★★ 4.51

Refrigeration System- Unitary : RTU-10  
Type

Number of bodies : 2

Body Material : Stainless Steel

Separate doors and handles : Yes  
for each chamber

Refrigerant Gas : R134A

Temperature Display : LED

Insulation Thickness : 75 millimeter  
[VIEW MORE](#)



GeMmy Standard  
COMPARE PRODUCT  
cabinet

ification

CE

Conformity to Electrical Safety  
Standard

IEC 60601 - 1

Manufacturer should be ISO  
certified

Yes

## Construction

Door Material

Stainless Steel

Refrigeration System- Unitary Type

RTU-10

Number of bodies

2

Trolley Material

Stainless steel

Body Material

Stainless Steel

## Technical Specification

Integral Temperature Gauge

Yes

Electronic temperature indicator

Yes



Ask GeMmy

PRODUCT COMPARE

PRODUCT HISTORY ②

*Accepted for*

Separate doors and handles for each chamber	Yes
Refrigerant Gas	R134A
Temperature Display	LED
Temperature of Mortuary Cabinet(degree celsius)	2 degC to 6 degC
Internal Lighting	Vapor proof incandescent lamp
Insulation Thickness	75 millimeter
Locking System	Standard Key Locks
Trolley sliding on telescopic rails	Yes
Defrosting Type	Automatic
Safety alarm	Audio, Visual
Insulation between the walls	High Grade Polyurethane
Type Of Alarm	Temperature Variation Alarm
Internal Drainage	Yes
Air Circulation	Axial Fan

**Ask GelMy**[PRODUCT COMPARE](#)[PRODUCT HISTORY](#) ②



Power Supply

Voltage, +/-10%

220 Volt

Phase

Single phase

Frequency

50 Hertz

Dimension & Size

Height

1420 millimeter

Width

850 millimeter

Height With Cooling Unit And Pcc Platform

1420 millimeter

Depth

2420 millimeter

Accessories

Optional Accessories

Stainless Steel tray,Caters,Stabilizer,Authorization Certificate,User manual



Ask GemMy

PRODUCT COMPARE

PRODUCT HISTORY ②

Compressor warranty

5 year

Warranty period

2 year

## Additional Parameter

Features

Trolley run on rollers fitted with ball bearings,Solid insulated doors,Spring door latch,Individual refrigeration system for each chamber,Molded lockable door catch with internal release,Removable Racks

Compressor is ISI Marked and CFC Free

Yes

Provision for simplified cadaver handling with maintenance of Hygiene

Yes

## Test Report

Test Report Date and Numbers  
(Please write NA if not applicable)

NA

Test Report To Be Submitted To The  
Buyer On Demand

NA

Availability of Test Report from  
Central Govt/NABL/ILAC accredited

No

 **Ask GeMmy** 'to

PRODUCT COMPARE

PRODUCT HISTORY ②



Type

Number of bodies : 1

Body Material : Stainless Steel

Separate doors and handles for each chamber : Yes

Refrigerant Gas : R134A

Temperature Display : LED

VIEW MORE Thickness : 50 millimeter

### Certification And Standard

Certification CE

Conformity to Electrical Safety Standard Equivalent International/National standard

Manufacturer should be ISO certified Yes

### Construction

Door Material Stainless Steel

Refrigeration System- Unitary Type RTU-06

Number of bodies 1

Trolley Material Stainless steel

Body Material Stainless Steel

Technical Specification



Ask GeMmy

PRODUCT COMPARE

PRODUCT HISTORY (4)

2, 11:21

Integral Temperature Gauge	Yes
Electronic temperature indicator cum controller	No
Separate doors and handles for each chamber	Yes
Refrigerant Gas	R134A
Temperature Display	LED
Temperature of Mortuary Cabinet(degree celsius)	-15 degC to 10 degC
Internal Lighting	Vapor proof incandescent lamp
Insulation Thickness	50 millimeter
Locking System	Standard Key Locks
Trolley sliding on telescopic rails	No
Defrosting Type	NA
Safety alarm	Visual
Insulation between the walls	High Grade Polyurethane
Type Of Alarm	Temperature Variation Alarm
Internal Drainage	Yes
Air Circulation	Forced Air Circulation

**Power Supply**

Voltage. +/-10% 230 Volt

**Ask GeMmy**

PRODUCT COMPARE

Single phase  
PRODUCT HISTORY (4)

*Book*  
*Asst Prof J. Anir*



25/03/2022, 11:21

Buy TEMPSTAR Stainless Steel Single phase Mortuary Cabinet, Warranty 1 year online | GeM

22.11.21

Test Report  
Number  
N

Frequency 50 Hertz

### Dimension & Size

Height 800 millimeter  
Width 800 millimeter  
Height With Cooling Unit  
And Pcc Platform 800 millimeter  
Depth 2000 millimeter

### Accessories

Optional Accessories User manual

### Warranty

Compressor warranty 1 year  
Warranty period 1 year

### Additional Parameter

Features Trolley run on rollers fitted with ball bearings  
Compressor is ISI Marked  
and CFC Free No  
Provision for simplified  
cadaver handling with  
maintenance of Hygiene No

Test Report

Test Report Date and  
Numbers (Please write  
NA if not applicable)

NA

Test Report To Be  
Submitted To The Buyer  
On Demand

NA

Availability of Test  
Report from Central  
Govt/NABL/ILAC  
accredited lab to prove  
conformity to  
specification

No

Name and Address of the  
lab (Please write NA if  
not applicable)

NA

## WEB INFO

[Terms of Use](#)[Website Policies](#)[Document Help](#)[Sitemap](#)[Web Information Manager](#)

## NEWS & EVENTS

[Newsroom](#)[Gallery](#)[Notifications](#)**Ask GeMmy**[PRODUCT COMPARE  
TESTIMONIALS](#)[PRODUCT HISTORY](#) (4)

## ABOUT GeM

[Introduction to GeM](#)[Statistics](#)[Right to Information](#)[Analytics](#)[New on GeM](#)[BRAND GeM](#)

## RESOURCES

[GeM Handbook](#)[OM's/Circulars](#)[Terms and Conditions](#)[Policies/Manuals](#)[Miscellaneous](#)[MOU'S](#)



# # Xerox Machine

Specification	Sub-Spec	Value
Ungrouped	Type of Machine	Multifunction Machine
	Print Technology	Laser
	Type of Printing	Mono
	Cartridge Technology	Separate Drum and Toner (Mono Component)
	Developer Unit	No
	Platen/Flatbed Size	A4
	Paper Size (Original/Image)	Legal/Legal
	RAM size (MB)	32
	Hard Disk Capacity(GB)	0
	Minimum Speed per Minute as per ISO/IEC 24734 in A4 Size-Mono	30
	Minimum Speed per Minute as per ISO/IEC 24734 in A4 Size-Colour	0
	Minimum Speed per Minute as per ISO/IEC 24734 in A3 Size-Mono	0
	Minimum Speed per Minute as per ISO/IEC 24734 in A3 Size-Colour	0
	Scanning Feature Availability	Yes
	Duplexing Feature Availability	Yes
	Faxing Feature Availability	No
	Speed of Fax, If Fax Feature is available	NA
	Networking Feature Availability	No
	If yes, Type of Network Interface	NA
	Wi-Fi Availability	No
	If yes,Wi-Fi Type	NA
	Original Document Feeder Type	Platen
	Feeder Capacity (Number)	1
	Number of Main Paper Tray	1
	Each Main Paper Tray Capacity (Number)	250
	Bypass Facility	Yes
	If Yes, Bypass Tray Capacity	1
	Yield of the cartridge/Ink Tank/Ink Pack supplied with Machine as per ISO/IEC: 19798/2007(E) for Cyan colour (Number of prints)	0
	Yield of the cartridge/Ink Tank/Ink Pack supplied with Machine as per ISO/IEC: 19798/2007(E) for Yellow colour (Number of prints)	0
	Yield of the cartridge/Ink Tank/Ink Pack supplied with Machine as per ISO/IEC: 19798/2007(E) for Magenta colour (Number of prints)	0
	Yield of the cartridge/Ink Tank/Ink Pack supplied with Machine as per ISO/IEC: 19752/2004(E) for Black (Number of prints)	2600
	Life of Drum in terms of number of Prints in case of Separate Drum and Toner cartridge technology - Cyan (Number of Prints)	0
	Life of Drum in terms of number of Prints in case of Separate Drum and Toner cartridge technology - Yellow (Number of Prints)	0
	Life of Drum in terms of number of Prints in case of Separate Drum and Toner cartridge technology - Magenta (Number of Prints)	0
	Life of Drum in terms of number of Prints in case of Separate Drum and Toner cartridge technology - Black (Number of Prints)	12000

Duty Cycle (No of Prints/month)	10000
Minimum Operating Temperature (Degree C)	10
Maximum Operating Temperature (Degree C)	32
Minimum Operating Humidity (%RH)	20
Maximum Operating Humidity (%RH)	80
BIS Registration under CRS of Melty	Yes
BIS Registration Number	R-41002208
Other Certifications Available	RoHS
Dimension (mm x mm x mm)	409x316.5x398.5
Weight (Kg)	9.75
On Site OEM Warranty (Year)	1



### 13. HARDWARE SPECIFICATIONS

Desktops	
Item	Description of Requirement
Mandatory Certifications	OEM – ISO 9001 Manufacturer, Certified on supplied OS, DMI 2.0 compliance and support, Energy Star 5, UL certification
Processor	5th Gen or higher Intel® Core™ i5 Processor
Core	Quad Core
Clock Speed	3 GHz or higher with turbo Frequency 3.50 GHz or higher
Cache	6 MB L2 or higher
Graphics	HD Graphics
Memory	Min. 4 GB (4 GB X1) 1600 MHz DDR3 / DDR4 Expandable to 16 GB
HDD	Min. 1 TB SATA 7200 rpm.
Monitor	19.7" LED TFT Digital Color Monitor from same OEM, TCO-05 certified
Keyboard	Standard 104 keys USB keyboard from same OEM
Mouse	USB, 2 Button Optical Scroll mouse from same OEM
Optical Device	DVD RW (Min. 16x)
Cabinet	Micro /Small Form Factor
USB	Min 4 External USB 2.0 and 2 USB 3.0 ports (Minimum 2 port on front panel),
Network Features	10/100/1000 on board integrated Network Interface with boot through LAN
Ports	Min 4 External USB 2.0 and 2 USB 3.0 ports (Minimum 2 port on front panel), VGA, HDMI, RJ45, Mic-in Headphone out (both in front & rear),
PCI Slot	Min 1 PCI/PCIe slot
Multimedia	Integrated Multimedia
Dust Cover	Quality Dust Cover
Operating System	Windows 10 pro (64Bits) English with 3 year of upgradable and patches until end of life by microsoft. Option to restore to factory setting through OEM
OS Certification	Window 7,8,10 & Linux compatible
Power Supply	SMPS with Surge protection and 90% Energy Efficiency



DMER & HBPCL, FSD Version 1.0	
Warranty	3 years NBD onsite service (3-3-3) on all system parts
Environment	Green PC with National/International certification for Energy Saving ( Energy Star or BEE)
Antivirus	Pre installed Anti-Virus with 3 yr updates, upgrades
200-114-1186	

Warranty	3 years NBD onsite service (3-3-3) on all system parts
Environment	Green PC with National/International certification for Energy Saving ( Energy Star or BEE)
Antivirus	Pre installed Anti-Virus with 3 yr updates, upgrades
600 MA UPS	



## **All in one Printer**


### **Specifications**

**(High End)**

1. A4 Black and White Laser Multifunction Printer, Perfect for Home and Office
2. Print, Copy and Scan
3. Print speed up to 21 ppm (black)
4. USB, Ethernet, Wi-Fi

## MULTIPARA MONITOR WITH NIBP AND ECG SPECIFICATIONS / VITAL SIGNS MONITOR

Display Size	12" LCD
Resolution	1280 x 800
Basic Parameter	ECG, SPO2, NIBP
Temperature Range	0–40°C (32–104°F)
Humidity Range	15–95% Relative Humidity
Ingress Protection	IP21
Power Consumption	<70w
Weight	6.6kg
Indicator	Alarm, ON, Error, External Power & Battery
USB 2.0 & RS232	available
ETCO2	Optional
IBP	optional
cardiac output	optional
NIBP Measurement technique	Step-deflation Oscillometric
Number of channels for NIBP	2
Blood pressure monitoring range Systolic	30-300mm or more /Hg
Diastolic BP	10-200 Or more
Gradation	±1 mm/Hg or better
Spo2 measurement range	40-100
Probe for Neonate	Reusable
Accuracy	±2 or better
Spo2 measurement technology	Massimo SET technology
Minimum Gradation	1%





Networking parameters	
Ethernet port	yes
Hardwired	yes
Connectivity provision with Central Nursing Station	yes
Standard accessories	
NIBP cuffs of small, medium , large and extra large for Adult, Pediatric and Neonate	3 each
Skin and Rectal temperature probe	2 each
EtCO2 cable/Module	yes
Accessories to wall mount the monitor	yes
IBP monitoring	All accessories for IBP monitoring at least in 2 patients (neonates and pediatric)
ECG cables	yes
Warranty (Option of comprehensive warranty is available through bidding only, which if opted will supersede normal warranty in the catalogue)	3 yrs

